



VIDEO INTERCOM



7" TOUCHSCREEN IP MONITOR WITH GESTURE AND VOICE COMMANDS REF. 1761/31

- Wall or flush mount
- 2Mpx camera
- Double input LAN and Wi-Fi
- Integrated management of Yokis radio building automation
- Possibility of managing building automation by other manufacturers
- Gesture command for the main features (touchless function)
- Voice command for most of the functions and scenarios



VIDEO INTERCOM

()(i)7" TOUCHSCREEN IP MONITOR WITH GESTURE AND VOICE COMMANDS

REF. 1761/31

Main features:

- Wall or flush mount
- 7" touchscreen display with resolution 1024 x 600
- Backlit Home button for notifications
- Full duplex audio
- 2Mpx Camera
- Double input LAN and Wi-Fi
- MicroSD card slot
- MUTE function with timing
- Integrated management of Yokis radio building automation
- Output for automatic recall
- Floor call input and alarm input
- Possibility of managing building automation by

other manufacturers

- Audio-video call services
- CCTV function on IP video cameras
- Image capture function
- Chat with other monitors
- Voice messaging
- Built in mifare reader
- Music player with possibility of using mp3 files as ring tones
- Brightness adjustment
- Volume adjustment for audio and ring tones
- Customisable background
- Language selection


2 ++


- Home page selection • Name directory

• 0

Ċ)

- Video codec H264 and audio codec G711 Compliant with SIP and RTSP standards
- PoE power supply
- Max consumption: 12W
- Temperature range: -5 +45 °C
- Wide view angle display: $160^{\circ} 160^{\circ} (H \times V)$
- Dimensions: 212 x 138 x 24 mm -8,34 x 5,43 x 0,74 in (9 mm - 0,35 in thickness for the flushmounted version)





COMPONENT DESCRIPTION:

- 1. Backlit blue Home button
- 2. Speakers
- 3. 7" touchscreen display
- 4. 2Mpx Webcam
- 5. Microphone
- 6. Micro SD Card

